

MSDS - Material Safety Data Sheet**Product Name: Basic Yellow, After Fuming Fluorescent Dye Spray**

MSDS No.: LVS500

I. Basic Information:

Manufacturer: Sirchie Finger Print Laboratories

Address: 100 Hunter Place

City, ST Zip: Youngsville, NC 27596

Emergency Contact: CHEMTREC

Emergency Telephone Number: 800-424-9300

Contact: Tech Support

Information Telephone Number: 919-554-2244

Last Update: 2-7-2008

Expiration Date:

Chemical State: Liquid Gas SolidChemical Type: Pure Mixture

2	Health
4	Flammability
1	Reactivity
H	Pers. Protection

II. Ingredients: Trade Secret

CAS No.	Chemical Name	% Range	EHS		IARC		SARA		OSHA PEL	ACGIH TLV	Other Limits
			NTP		SUB Z	313					
67561	Methanol	>99					X	200 ppm	200 ppm	53.6 F	

III. Hazardous Identification:

Hazard Category:

 Acute Chronic Fire Pressure Reactive
Hazardous Identification Information:

FLAMMABLE! May be fatal or cause blindness if ingested. Harmful if inhaled. May be absorbed through the skin. May cause respiratory and digestive tract irritation. Skin and eye irritant. May cause central nervous system depression. May cause liver and kidney damage. May cause adverse reproductive and fetal effects based on animal testing.

This material is subject to the reporting requirements of Section 313 of SARA Title III and 40 CFR Part 373.

IV. First Aid Measures:**Route(s) of Entry:**

Inhalation, ingestion, skin, eyes

Health Hazards (Acute and Chronic):

Chronic: Dermatitis

Signs and Symptoms:

Inhalation: Headache, convulsions, death

Ingestion: Excitement, headache, dizziness, drowsiness, nausea, collapse, unconsciousness, coma, death due to respiratory failure

Medical Conditions Generally Aggravated by Exposure:

Kidney, central nervous system, liver, eyes, respiratory, skin diseases

MSDS - Material Safety Data Sheet

Product Name: Basic Yellow, After Fuming Fluorescent Dye Spray

MSDS No.: LVS500

Emergency and First Aid Procedures:

Inhalation: Remove to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult, give oxygen (To be administered by qualified medical personnel only!) Get medical attention.

Ingestion: If victim is conscious and alert, give 2-4 cups of milk or water. (Never give anything by mouth to an unconscious person!) Induce vomiting by giving one teaspoon (1 tsp.) of syrup of ipecac. Get medical attention immediately.

Skin: Flush skin with plenty of soap and water for at least 15 minutes. Remove contaminated clothing. Seek medical attention if irritation persists.

Eyes: Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower lids. Do not allow victim to rub or keep eyes closed. Get medical aid immediately.

Notes to physician: Effects may be delayed. Ethanol may inhibit metabolism.

Other Health Warnings:

V. Fire Fighting Measures:

Flash Point: 53.6 F

Lower Explosive Limit: 6.00 vol%

Upper Explosive Limit: 31.00 vol%

F.P. Method:

Fire Extinguishing Media: Dry chemical, carbon dioxide, water spray, alcohol-resistant foam

Special Fire Fighting Procedures:

Wear self-contained breathing apparatus and protective clothing. Remove containers from fire area if possible to do so without risk. Water may be ineffective, but may be used to cool fire-exposed containers. Apply cooling water to sides of fire-exposed containers until well after fire is out.

Unusual Fire and Explosion:

Containers can build up pressure if exposed to heat and/or fire. Vapors from this product may travel some distance from original point to an ignition source and flash back.

"Empty" containers may contain product residue and may be dangerous. Empty containers should be completely drained and bunged and then disposed of according to local, state, and federal regulations.

VI. Accidental Release Measures:

Steps to be Taken in Case Material is Released or Spilled:

Do not walk through spilled material. Wear vapor respirator, safety goggles, and rubber gloves. Remove sources of ignition (i.e. open flames, sparks). Stop leak at source if possible to do so without risk. Soak up with inert absorbent material (earth, sand, or vermiculite recommended; do not use flammable substances such as sawdust). Scoop up with non-sparking tool. Scrub spill area with detergent and flush with copious amounts of water. Dispose according to local, state, and federal regulations.

VII. Handling and Storage:

Precautions to be Taken:

Keep in closed container. Keep cool and dry. Avoid all ignition sources (heat, open flame, spark). Avoid incompatible materials. Use only in well-ventilated areas. Avoid contact with skin and eyes. Do not ingest or inhale. Wash thoroughly after handling.

Other Precautions:

"Empty" containers may contain product residue and may be dangerous. Empty containers should be completely drained and bunged and then disposed of according to local, state, and federal regulations.

MSDS - Material Safety Data Sheet

Product Name: Basic Yellow, After Fuming Fluorescent Dye Spray

MSDS No.: LVS500

VIII. Exposure Controls/Personal Protection:

Ventilation Requirements:

Use only in well-ventilated areas.

Personal Protective Equipment:

Safety goggles, gloves, vapor respirator, protective clothing

IX. Physical and Chemical Properties:

Boiling Point: 64.7 C

Melting Point: -98 C

Evaporation Rate (Butyl Acetate = 1): 5.2

Vapor Pressure (mm Hg.): 96

Specific Gravity (H2O = 1):

Vapor Density (AIR = 1): 1.1

Solubility In Water: Miscible

Appearance and Odor:

Other Information:

X. Stability and Reactivity:

Stability:

Stable at room temperature in closed containers under normal storage and handling conditions.

Incompatibility (Materials to Avoid):

Oxidants, active metals, acetyl bromide, alkyl aluminum salts, beryllium dihydride, carbon tetrachloride + metals, chloroform + heat, chloroform + sodium hydroxide, cyanuric chloride, diethyl zinc, nitric acid, potassium tertbutoxide, ignition sources (heat, open flame, spark). Please refer to the NFPA Fire Protection Guide for all methanol incompatibility specifics.

Decomposition/By Products:

Carbon monoxide, carbon dioxide, formaldehyde (carcinogen)

Hazardous Polymerization:

Has not been reported.

XI. Toxicological Information:

May be fatal if swallowed. Harmful if inhaled. May be absorbed through the skin in harmful amounts. May cause central nervous system depression. May cause liver and kidney damage. May cause adverse reproductive and fetal effects based on animal studies.

XII. Ecological Information:

Prevent from entering sewers or waterways. May be toxic to some aquatic life.

XIII. Disposal Considerations:

Dispose according to local, state, and federal regulations.

Methanol

RCRA U-Series: Waste no. U154 (Ignitable waste)
This material is banned from land disposal according to RCRA.

MSDS - Material Safety Data Sheet

Product Name: Basic Yellow, After Fuming Fluorescent Dye Spray

MSDS No.: LVS500

XIV. Transport Information:

Keep in closed container. Keep cool and dry. Avoid all ignition sources (heat, open flame, spark). Avoid incompatible materials. Avoid contact with skin and eyes. Do not ingest or inhale. Wash thoroughly after handling.

IATA

Shipping name: Methanol solution

Hazard class: 3

Sub-Class: 6.1

UN no.: 1230

Packing group: II

Flammable liquid!

XV. Regulatory Information:

Methanol is listed on the TSCA inventory.

Methanol is listed as a hazardous air pollutant (HAP) under the Clean Air Act.

This material is subject to the reporting requirements of Section 313 of SARA Title III and 40 CFR Part 373.

XVI. Other Information:

Using this product under normal, properly instructed procedures should not be hazardous.

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, expressed or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigation to determine the suitability of the information for their particular purposes.